

# Zagers

BRAND

## Z 310

### HIGH PRODUCTIVITY STRIPPER

Vinyl Asbestos  
Linoleum  
Rubber  
Terrazzo



Vinyl  
Concrete  
Flagstone  
Ceramic Tile

#### Product Description

A new generation floor finish stripper that rapidly penetrates and solubilizes floor finish. Powerful solvents combined with penetrating amines dissolve the finish on contact, reducing the waiting periods for removal of the finish. This product completely evaporates from the surface. Can be used with or without a floor machine.

#### NOTE:

As prolonged soaking in concentrated strippers may damage some asphalt tiles, a spot test is recommended before general use.

#### Test:

#### Limit:

<b>Active Ingredients:</b>	55.0 ± 0.5%
<b>Color:</b>	Red
<b>Odor:</b>	Sassafras
<b>pH(concentrate):</b>	12.5 - 13.0
<b>Viscosity:</b>	Water thin
<b>Foam:</b>	Low
<b>Abrasives:</b>	None
<b>Phosphate Content:</b>	None
<b>Solubility:</b>	Complete with water
<b>Emulsification:</b>	Excellent
<b>Detergency:</b>	Excellent
<b>Rinsability:</b>	Excellent
<b>Flash Point:</b>	145°F (TCC)
<b>Biodegradability:</b>	Complete
<b>Storage/Stability:</b>	2 years
<b>Weight Per Gallon:</b>	8.27 lbs. per gallon
<b>Freeze / Thaw Stability:</b>	Keep from freezing

#### Directions For Use

#### MOP/WET VACUUM STRIPPING SYSTEM:

Dilute in cold or mildly warm water according to the type of finish below:  
One part product to 2 parts water for heavily built-up or highly burnished finishes.  
One part product to 5 parts water for normal build-up.

Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 2 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of new finish.

#### FLOOR MACHINE STRIPPING SYSTEM:

Dilute in cold or mildly warm water according to the type of finish below:  
One part product to 10 parts water for heavily built-up or highly burnished finishes.  
One part product to 15 parts water for normal build-up.

Product may be applied with a mop or Automatic Scrubber. Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow the floor to dry completely. If desired, a deep rinsing step can be added. Apply new finish per manufacturer recommendation.

